

PRODUCT DATA

PACKAGING

492 ft² Rolls (39.36" x 150')

COVERAGES

Coverage rates will vary depending on use and application. Please refer to the desired System Specification for coverage rates.

COLOR

Gray

SHELF LIFE

The shelf life is 5 years from the date of manufacture, when properly stored in the original, unopened container.

TECHNICAL DATA

VOC CONTENT

0 g/L

WEIGHT

8.8 oz (Sq. Yd.)



PRODUCT DESCRIPTION

MK-71 Shur Deck Glass Lath is an alternative glass lath option, designed to be used in lieu of traditional metal lath.

USES

MK-71 is designed to be used in the Base Coat of the Shur Deck system. The MK-71 features a leno weave that helps promote proper embedment of the MK-5 Shur Deck Cement. This non-metal, glass lath is ideal for use in coastal areas or where enhanced corrosion resistance is required.

ADVANTAGES

- Excellent dimensional stability
- Reinforces the Base Coat
- Helps aid in application thickness
- Non-Metal

INSPECTION

Surface must be structurally sound, dry, and free of laitance, oil, grease, curing agents, dirt, dust or other foreign material that may prevent proper adhesion.

PREPARATION

Please refer to the desired System Specification Sheet for further information regarding Surface Preparation. Surface should be prepared per industry standard.

APPLICATION

Please refer to the desired System Specification Sheet for further information regarding Application. For maximum corrosion resistance, stainless steel fasteners are recommended when using MK-71. Note that when MK-71 is used in lieu of MK-70 Shur Deck Metal Lath, Base Coat coverage rates for the Shur Deck system will be reduced from 45 sq. ft. to ~30 sq. ft. per mix.

CAUTION & LIMITATIONS

- The substrate surface must be structurally sound, clean, dry and free of laitance, dirt, dust, oil, grease, paint or other contaminants at the time of material application.
- Substrate and ambient temperature must be above 55°F and below 90°F during and for 24 hours following the application.
- Do not apply in inclement weather, when rain is occurring or expected within 24 hours.
- Designed for professional use.

STORAGE & HANDLING

Store all materials off the ground in a dry environment at temperatures between 50°F and 90°F and not in direct sunlight. All materials should be stored in compliance with local fire and safety requirements. Always wear proper safety equipment, including particle mask, eye protection and gloves when mixing and/or applying these products.

HEALTH PRECAUTIONS

Inhalation of vapor or mist can cause headache, nausea, irritation of nose, throat and lungs. Prolonged or repeated skin contact can cause slight skin irritation. Wear rubber gloves and eye protection. Avoid eye contact and prolonged contact with skin. Wash thoroughly after handling. If eye contact occurs, flush with water for 15 minutes. Call a physician immediately.

DISCLAIMER

Purchaser's sole and exclusive remedy against the manufacturer of Mer-Ko, shall be limited solely to the replacement of any defective material or a payment by the manufacturer in an amount equal to the cost of the original material.